

Product Data Sheet

Cromadex Liquid Coatings

Cromadex 800 Aerosol

Two Pack Non-Isocyanate Acrylic Topcoat Aerosol

Product Description

Cromadex 800 is a two pack non-isocyanate acrylic topcoat aerosol for touch up.

Fast drying	Available in 4 gloss levels
Exterior durable	Isocyanate-free
8 hour pot life	Lead and chromate-free

Surface Preparation

The surface should be clean, dry and free of grease. Sound existing paintwork, including powder coating, should be degreased and abraded with P280 prior to painting.

Can be applied over any Cromadex aerosol primer as well as many of the standard liquid primers in the Cromadex range.

Further details regarding suitable primers and for larger scale finishing using Cromadex 800, please see the Cromadex 800 datasheet.

Application Details



- (1) Before use, remove the base of can
- (2) Attach the ring to the plunger and pull down
- (3) Turn the ring/plunger through 360° to release the curing agent

Shake the aerosol for 2 minutes and spray a sample. Distance to the surface should be approximately 20 centimetres.

Nozzle has a variable spray fan to allow for extra fine finishing.

Apply in thin layers. Between coats, re-shake aerosol.

Drying

Dust Dry	After 5-10 minutes
Tack Free	After 10-20 minutes
Hardened/ Resprayable	After 2 hours

Physical Properties

Coverage	1.5 – 2.0 m ² per aerosol
VOC	Approx 18% w/w

Safety Precautions and Disclaimer

Before using this product please refer to the Cromadex Material Safety Data Sheet.

The information contained in this data sheet is not intended to be exhaustive, and any person using the product without first obtaining written confirmation from us as to the suitability of the product for the intended purposes, does so at their own risk. Whilst we endeavour to ensure that all advice we give about the product (whether in this sheet or otherwise) is correct, we have no control over either the quality or condition of the substrate or the many factors affecting the use and application of the product. Therefore, unless we specifically agree to do so, we do not accept any liability whatsoever arising from the performance of the product or for any loss or damage (other than death or personal injury resulting from our negligence) arising out of the use of this product. The information contained in this sheet is liable to modification from time to time in the light of experience and our policy of continuous product development.

It is the user's responsibility to check that this data sheet is current prior to using the product.