

Product Data Sheet

Cromadex Liquid Coatings

Cromadex 678 Spirit Wipe

| Braduat Description | Formulated to remove all traces of all and graces from metal surfaces prior to pointing |
|--------------------------------------|--|
| Product Description | Formulated to remove all traces of oil and grease from metal surfaces prior to painting. Recommended for manual cleaning where vapour degreasing is not suitable, product is supplied ready |
| | for use. |
| Preparation | Any rust or other foreign chemical compound on metal should first be removed by abrading. |
| Application | Use a brush or clean cloth, the 678 Spirit Wipe should be liberally applied to the substrate. It is important to regularly change the cloth to avoid returning grease to the surface. Clean gloves should be worn when handling surfaces which have been degreased. |
| | Note : Once degreased, it is recommended that articles are primed with the minimum of delay to prevent corrosion of the exposed metal. |
| voc | VOC content of this product in ready to use form is max. 750 g/l. |
| Flash Point | Flash point below 21°C. |
| Storage | Store between 5° C – 35° C for a period not exceeding twelve months before use. |
| | Note: When not in use cans must be kept sealed. |
| Safety | Always provide adequate ventilation during cleaning and degreasing. Where reasonably practicable, this should be achieved by the use of local exhaust ventilation and good general extraction. If these are not sufficient to maintain concentrations of particulates and solvent vapours below the OEL, suitable respiratory protection must be worn. Besides respiratory protection, always wear solvent resistant gloves while cleaning or degreasing even though working with a low solvent degreaser. This will reduce the risk of cleaning solvents being absorbed into the skin and prevent salts and oils on your hands from contaminating the surface to be painted. This product is not formulated as a skin cleansing material nor should it be used for cleaning clothing or any protective equipment. Do not use on electrical equipment or cables. |
| Safety Precautions and Disclaimer | Before using this product please refer to the Cromadex Material Safety Data Sheet. The information contained in this data sheet is not intended to be exhaustive, and any person using the product without first obtaining written confirmation from us as to the suitability of the product for the intended purposes, does so at their own risk. Whilst we endeavour to ensure that all advice we give about the product (whether in this sheet or otherwise) is correct, we have no control over either the quality or condition of the substrate or the many factors affecting the use and application of the product. Therefore, unless we specifically agree to do so, we do not accept any liability whatsoever arising from the performance of the product or for any loss or damage (other than death or personal injury resulting from our negligence) arising out of the use of this product. The information contained in this sheet is liable to modification from time to time in the light of experience and our policy of continuous product development. It is the user's responsibility to check that this data sheet is current prior to using the product. |

