

# Product Data Sheet

## Cromadex Liquid Coatings Cromadex Super Build Primer Aerosol

<b>Product Description</b>	<p>Cromadex Super Build Primer is a high quality, very fast drying build primer. This results in an easily sanded non-porous surface that is suitable for a wide range of topcoats</p> <p>The product has good adhesion to bare metal, excellent coverage and filling properties, and is easy to sand both wet and dry (from P400).</p>										
<b>Usage</b>	<p>Before use, carefully read the directions on the packaging and act accordingly.</p>										
<b>Pre-Treatment</b>	<p>The surface should be clean, dry and free of grease. Remove loose old lacquer and rust and sand the surface.</p>										
<b>Treatment</b>	<p>The surface should be clean, dry and free of grease. The aerosol should have room temperature. Best processing temperature 15 to 25°C. Before use, shake the aerosol for 2 minutes and spray a sample. Distance to the surface to be treated approximately 25 centimetres.</p> <p>Apply the Super Build Primer in several layers allowing 3-5 minutes between coats. Before applying the next layer, re-shake the aerosol.</p> <p>After use, clean the valve (turn aerosol upside down and press the nozzle for approximately 5 seconds).</p>										
<b>Drying</b>	<table border="0"> <tr> <td><b>Dust Dry</b></td> <td>After 5-10 minutes</td> </tr> <tr> <td><b>Tack Free</b></td> <td>After 10-20 minutes</td> </tr> <tr> <td><b>Overcoatable</b></td> <td>After 15-30 minutes</td> </tr> </table> <p>The drying time depends on the ambient temperature, the humidity of the air and the thickness of the lacquer applied.</p>	<b>Dust Dry</b>	After 5-10 minutes	<b>Tack Free</b>	After 10-20 minutes	<b>Overcoatable</b>	After 15-30 minutes				
<b>Dust Dry</b>	After 5-10 minutes										
<b>Tack Free</b>	After 10-20 minutes										
<b>Overcoatable</b>	After 15-30 minutes										
<b>Physical Properties</b>	<table border="0"> <tr> <td><b>Sandable</b></td> <td>With P400 – P500</td> </tr> <tr> <td><b>Heat Resistant</b></td> <td>Up to 110°C</td> </tr> <tr> <td><b>Solid Content</b></td> <td>Approx 22% w/w</td> </tr> <tr> <td><b>VOC Content</b></td> <td>Approx 78% w/w</td> </tr> <tr> <td><b>Colour</b></td> <td>Grey</td> </tr> </table>	<b>Sandable</b>	With P400 – P500	<b>Heat Resistant</b>	Up to 110°C	<b>Solid Content</b>	Approx 22% w/w	<b>VOC Content</b>	Approx 78% w/w	<b>Colour</b>	Grey
<b>Sandable</b>	With P400 – P500										
<b>Heat Resistant</b>	Up to 110°C										
<b>Solid Content</b>	Approx 22% w/w										
<b>VOC Content</b>	Approx 78% w/w										
<b>Colour</b>	Grey										
<b>Safety Precautions and Disclaimer</b>	<p><b>Before using this product please refer to the Cromadex Material Safety Data Sheet.</b></p> <p>The information contained in this data sheet is not intended to be exhaustive, and any person using the product without first obtaining written confirmation from us as to the suitability of the product for the intended purposes, does so at their own risk. Whilst we endeavour to ensure that all advice we give about the product (whether in this sheet or otherwise) is correct, we have no control over either the quality or condition of the substrate or the many factors affecting the use and application of the product. Therefore, unless we specifically agree to do so, we do not accept any liability whatsoever arising from the performance of the product or for any loss or damage (other than death or personal injury resulting from our negligence) arising out of the use of this product. The information contained in this sheet is liable to modification from time to time in the light of experience and our policy of continuous product development.</p> <p>It is the user's responsibility to check that this data sheet is current prior to using the product.</p>										